

SUCTION & DISCHARGE HOSE

Specification	A65, A66, A67, A68 – Hand-built ‘hard wall’ suction and discharge hose.									
Applications	Fuels, oils, seawater, water, mud, dry powders, cement, sand, gravel.									
Sizes	50mm to 400mm – 12 metres. 450mm to 600mm – 7 metres.									
Lining	Natural	NR				Water, medium abrasives				
	Nitrile	NBR				Fuels, oils				
	Neoprene	CR				Seawater, oil based mud				
	EPDM	EP				Chemicals, seawater				
	¼” thick natural rubber	NRT				Heavy abrasives				
	Hypalon	CSM				Chemicals				
	Viton®	FPM				Special applications				
	WRCA EPDM	WRCA				Drinking water				
Consult JH Hose for the correct lining to suit your application										
Reinforcement	Multiple layers of synthetic cord plus a single steel wire helix, giving a minimum 3.5:1 safety factor and a minimum 6 x bore size bend radius.									
Working pressure/ vacuum	A65	3.5 bar				-0.85 bar				
	A66	7 bar				-0.85 bar				
	A67	10 bar				-0.85 bar				
	A68	15 bar				-0.85 bar				
Hose assemblies are tested to 1.5 x working pressure										
Cover	Tough abrasion and weather resistant corrugated neoprene rubber.									
Approximate weight Kg/metre	Size	A65	A66	A67	A68	Size	A65	A66	A67	A68
	2”	3	3	3	3	12”	22	24	24	26
	3”	4	4	4	4	14”	33	35	37	38
	4”	5	5	6	6	16”	35	37	38	40
	6”	10	11	11	12	20”	47	48	52	56
	8”	17	17	17	18	22”	54	60	65	79
	10”	19	21	21	23	24”	60	65	70	81
Other sizes are available on request										
Coupling systems	Wired-in, clamps, vulcanised and built-in, swaged, integral fixed rubber and fabric flanges with steel backing plates, beaded swivel ends, cuffs.									

MULTIPURPOSE

JFHOSE

DELIVERY HOSE

Specification	A70, A71, A72, A73 – Hand-built ‘soft wall’ delivery hose.									
Applications	Fuels, oils, seawater, water, mud, dry powders, cement, sand, gravel.									
Sizes	50mm to 400mm – 12 metres. 450mm to 600mm – 7 metres.									
Lining	Natural	NR				Water, medium abrasives				
	Nitrile	NBR				Fuels, oils				
	Neoprene	CR				Seawater, oil based mud				
	EPDM	EP				Chemicals, seawater				
	¼” thick natural rubber	NRT				Heavy abrasives				
	Hypalon	CSM				Chemicals				
	Viton®	FPM				Special applications				
	WRCA EPDM	WRCA				Drinking water				
Consult JH Hose for the correct lining to suit your application										
Reinforcement	Multiple layers of synthetic cord designed to give pressure resistance, flexibility and stability under pressure. When pressurised, hoses have a bend radius of 8 x bore size and a minimum 3.5: 1 safety factor.									
Working pressure	A70					3.5 bar				
	A71					7 bar				
	A72					10 bar				
	A73					15 bar				
Hose assemblies are tested to 1.5 x working pressure										
Cover	Tough abrasion and weather resistant corrugated neoprene rubber.									
Approximate weight Kg/metre	Size	A70	A71	A72	A73	Size	A70	A71	A72	A73
	2”	1.5	1.5	1.5	1.5	12”	12	15	17	19
	3”	2	2	2	2	14”	16	19	22	29
	4”	3	3	4	4	16”	18	22	28	35
	6”	5	5	6	6	20”	23	31	39	47
	8”	7	8	9	9	22”	27	36	45	55
	10”	10	10	12	14	24”	32	41	51	65
Other sizes are available on request										
Coupling systems	Wired-in, clamps, vulcanised and built-in, swaged, integral fixed rubber and fabric flanges with steel backing plates, beaded swivel ends, cuffs.									

JF Hose & Couplings Limited, Unit 5, Hecla Works, Mounsey Road, Bamber Bridge, Preston, PR5 6LS
Tel: +44(0)1772 323300 Fax: +44(0)1772 323322 Email: sales@jfhose.co.uk www.jfhose.co.uk
Registered to BS EN ISO 9001:2008. Viton® rubber is a registered trademark of Dupont Performance Elastomers